

KolorLok 10's paint process is formulated with pigments that greatly reduce the risk of distortion and warping of vinyl material caused by heat gain. Our paint process meets both AAMA 613-98 and AAMA 615 requirements. These tests include: Color Uniformity, Chemical Resistance, Cold Crack Cycling, Heat Build-Up, Solvent Resistance, Humidity Resistance, and Outdoor Weathering

VLAM's Laminated 3-layer weather-foil wrap is like no other of its kind and designed for use in extreme climate zones. VLAM cool color technology prevents the sun's radiation from penetrating into the vinyl as it is reflected off the surface

Both KolorLok 10 (Paint) and VLAM (Laminate) is guaranteed to the original homeowner to resist cracking, peeling, flaking, checking, delaminating and blistering for a period of ten (10) years from original date of manufacturing. Failures or defects not covered are normal wear and tear of components, improper storage, alterations, abuse, misuse, neglect, installation and maintenance, or abnormal conditions. Power or chemical washing may have adverse effects on the exterior surface of the window, this will void the warranty for defects incurred. In the event of failure, a claim must be submitted in writing within forty-five (45) days of the first indication of coating failure. The following information should be included in correspondence: Date of Purchase, Dealer Name (Who Installed the Windows), Location on Window or Door where Suspected Failure has taken place, Color or Coating, and Photographs of Suspected Coating Failure.





info@vinylkraft.com



